

# CAREU Ueco

Economic GPS Tracker



## Features

- › Cost effective and easy installation
- › Two-way voice environment listening \*
- › Data communications by UMTS/HSPA/GPRS/EDGE, SMS, FTP, USSD
- › Support GPS/ Glonass \* / BDS \* / Galileo \* Satellite System
- › Built-in 3-axis accelerometer
- › Support harsh acceleration/ harsh braking/Impact detection
- › Support 1-Wire® interface temperature function and i-Button driver ID
- › Geofence report in circular and polygonal types
- › Remote configuration
- › Configurable real-time tracking.
- › Intelligent power management
- › GPS Odometer data reading and rich user-defined reports
- › FOTA firmware via FTP
- › Power low/lost alarm
- › GSM jamming detection
- › GPS antenna tamper detect alarm
- › Maximum 200,000 data logs

(\*) Optional




## Advantages

- 2G or 3G Network**
- eCall System (112)**
- 1-Wire® Interface**
- Assisted-GPS (Ephemeris)**
- Multi Satellite System (GNSS)**
- Harsh Driving Behavior Detection**
- Automatic Self-Diagnostic Record**



SYSTEMS & TECHNOLOGY CORP.  
[www.systech.com.tw](http://www.systech.com.tw)



## Specifications

- › Communication Specification
  - Frequency
    - 2G/GSM : Quad band, 850/900/1800/1900 MHz
    - 3G/ UMTS/HSPA : 850/900/1900/2100 MHz
  - Data Protocol : TCP, UDP, SMS, Voice, USSD
- › GNSS Performance
  - Datum : WGS-84
  - Receiver type : 72 channels
  - Sensitivity : -167 dBm; 26s
- › General Specification
  - Dimensions (L x W x H) : 72mm x 105.5mm x 28.5mm
  - Weight : 80g
  - Power Source : 8-30V DC
  - Power Consumption :
    - 49mA@12V DC (Operating Mode)
    - 10mA@12V DC (Standby Mode)
    - 6mA@12V DC (Sleep Mode)
- › Operating Temperature : -20°C~+70°C (-4°F~158°F)
- › Interface
  - Input Ports :
    - 1 x ACC/Ignition Input
    - 3 x Digital Inputs (1 x Positive trigger & 2 x Negative triggers)
    - 1 x Analog Input (12-bit resolution)
    - 1 x 1-Wire® Input
  - Output Ports : 2 x Outputs (Max. sink current 300mA)
  - Two-way voice port \*

( \*) Optional

## Accessories

### Standard

- › Power & I/O cable
- › GPS antenna

### Option

- › Backup battery : Li-ion, 160mAh
- › USB cable
- › Microphone kit
- › i-button
- › Temperature sensor

## Applications

- › Vehicle real-time tracking
- › Vehicle security/rescue/anti-hijack
- › Mobile asset tracking
- › Fleet management
- › Location based service

The specification may be subjected to change without prior notice.



SYSTEMS & TECHNOLOGY CORP.

3F-7, No.79, Sec.1, Hsin-Tai Wu Road, Hsichih Dist., New Taipei City 22101, Taiwan, R.O.C.  
TEL : +886 2 2698 1599 FAX : +886 2 2698 1211 Email : avl@systech.com.tw

2019.05